

X-Link WL Surface Sealer (wet look) Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name. : X-Link WL Surface Sealer (wet look)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Semi penetrating cementitious stain protector

1.3. Details of the supplier of the safety data sheet

Ameripolish 120 Commercial Ave Lowell, AR 72745 T 479-725-0033

1.4. Emergency telephone number

Emergency number : Chemtel 800-255-3924

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Irrit. 2 H315 Eye Irrit. 2A H319

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)



GHS07

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H315 - Causes skin irritation

H319 - Causes serious eye irritation

Precautionary statements (GHS-US) : P264 - Wash ... thoroughly after handling

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P302+P352 - IF ON SKIN: Wash with plenty of soap and water

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing P321 - Specific treatment (see ... on this label)

P332+P313 - If skin irritation occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention

P362 - Take off contaminated clothing

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Proprietary Component 1	(CAS No) Trade Secret	Trade Secret	Not classified
Proprietary Component 2	(CAS No) Trade Secret	Trade Secret	Not classified
Proprietary Component 3	(CAS No) Trade Secret	Trade Secret	Not classified
Proprietary Component 4	(CAS No) Trade Secret	Trade Secret	Acute Tox. 3 (Oral), H301 Skin Corr. 1A, H314
Proprietary Component 5	(CAS No) Trade Secret	Trade Secret	Not classified

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Adverse effects not expected from this product.

01/08/2014 EN (English) Page 1

X-Link Surface Sealer

Safety Data Sheet

First-aid measures after skin contact : Flush with water for at least 15 minutes. Seek medical attention if irritation develops or persists.

First-aid measures after eye contact : Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists get

medical attention.

First-aid measures after ingestion : Do NOT induce vomiting. Seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : None under normal use.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray, dry chemical, foam, carbon dioxide.

Unsuitable extinguishing media : None.

5.2. Special hazards arising from the substance or mixture

Fire hazard : None known. Explosion hazard : None known.

5.3. Advice for firefighters

Protection during firefighting : Firefighters should wear full protective gear.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Stop the flow of material, if this is without risk.

Methods for cleaning up : Confine spill and soak up with absorbent. Place in an approved container and dispose in

accordance with local, state and federal regulations.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : No special storage conditions required.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Proprietary Component 4		
USA ACGIH	ACGIH Ceiling (mg/m³)	2 mg/m³

8.2. Exposure controls

Appropriate engineering controls : Provide adequate general and local exhaust ventilation.

Hand protection : Use impervious gloves such as neoprene, nitrile, or rubber for hand protection.

Eye protection : Chemical goggles or safety glasses. Skin and body protection : Wear suitable working clothes.

Respiratory protection : If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

01/08/2014 EN (English) 2/5

X-Link Surface Sealer

Safety Data Sheet

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : Milky White
Odour : odorless.
Odour threshold : 8.6

: No data available Relative evaporation rate (butylacetate=1) : No data available : No data available Melting point : No data available Freezing point : No data available **Boiling point** Flash point : No data available Self ignition temperature : No data available Decomposition temperature : No data available : No data available Flammability (solid, gas) Vapour pressure : No data available Relative vapour density at 20 °C : No data available

Relative density : 1.4 g/ml

: No data available Solubility Log Pow : No data available Log Kow : No data available : No data available Viscosity, kinematic : No data available Viscosity, dynamic Explosive properties : No data available Oxidising properties : No data available : No data available Explosive limits

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

None.

10.5. Incompatible materials

Not determined.

10.6. Hazardous decomposition products

Not determined.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Proprietary Component 4		
LD50 oral rat	214 mg/kg	
Skin corrosion/irritation	: Causes skin irritation.	
Serious eye damage/irritation	: Causes serious eye irritation.	
Respiratory or skin sensitisation	: Not classified	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
Reproductive toxicity	: Not classified	
01/09/2014	EN (English)	2/5

01/08/2014 EN (English) 3/5

X-Link Surface Sealer

Safety Data Sheet

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Proprietary Component 4	
LC50 fishes 1	80 mg/l (Exposure time: 96 h - Species: Gambusia affinis [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Proprietary Component 4	
Log Pow	0.65

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations

: Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

In accordance with DOT / ADR / RID / ADNR / IMDG / ICAO / IATA

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Proprietary Component 2

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Proprietary Component 4

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Proprietary Component 3

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Proprietary Component 1

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Proprietary Component 5

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State regulations

Proprietary Component 4

- U.S. Massachusetts Right To Know List
- U.S. Minnesota Hazardous Substance List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases::

Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Skin Corr. 1A	skin corrosion/irritation Category 1A

01/08/2014 EN (English) 4/5


X-Link Surface Sealer Safety Data Sheet

Skin Irrit. 2	skin corrosion/irritation Category 2
H301	Toxic if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation

: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given. NFPA health hazard

NFPA fire hazard : 0 - Materials that will not burn.

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water. NFPA reactivity



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

01/08/2014 EN (English) 5/5