



Shot Blasting Systems

WALK-BEHIND AND SELF-PROPELLED

Blastrac® 2-20DT Global

The Blastrac® 2-20DT Global is a powerful self-propelled 20" shot blasting system, ideal for medium to larger sized jobs. Whether improving traction and skid resistance or prepping for coatings and overlays, the versatile 2-20DT Global strips, cleans and profiles concrete and asphalt in one easy step.

The AC inverted drive-motor for self-propelled operation features an integrated brake which helps maintain speed on ramps and inclines. This improves productivity and promotes a more even and consistent blast pattern and surface profile. Attached to the 8-54DC or other suitable Blastrac dust collector, it operates virtually dust-free. A slide-out screen in the shot hopper facilitates the removal of large debris.

The 2-20DTSG can prepare up to 4850 sq. ft. per hour* consuming abrasive at about 1.6 lb. per 100 sq. ft. or 78 lb. per hr. The quick-lift rear caster assembly makes this 1268 lb. unit easily transportable. It has highly visible and manageable controls with the drive control on the steering handle. The 2-20DTG operates on 460V, three-phase, and all electrical components and panels are UL certified, part of Blastrac's commitment to safety protocol.

Perfect for industrial floors, warehouses, road and airport maintenance, and parking garages, this shot blaster is an environmentally sound choice for high productivity in surface preparation.



Controls are easy to access with drive adjustments on steering handle.



Blastrac
2-20DT Global

Blastrac® 2-20DT Global

FEATURES & BENEFITS:

- Easily maneuverable, self-propelled machine—forward and reverse
- AC inverted drive-motor with integrated brake for even, down-slope operation on ramps and inclines
- Quick-lift rear caster assembly for easier transporting
- Highly versatile and appropriate for medium to large job sites
- Excellent for industrial floor prep, road and airport maintenance, ship decks, decontamination, and more
- Labor and time-saving shot blasting process strips, cleans and profiles in one step—cost effective and friendly to the environment
- Operates virtually dust-free when connected to the Blastrac 8-54 or 955DC dust collector—healthier for the operator and coworkers

SPECIFICATIONS:

Blasting Width: 20 in. (550mm)
Travel Speed: Up to 108 ft/min. (33m/min)
Prod. Capacity¹: Up to 4850 sq.ft/hr (450m²/h) on concrete
Blast Motor: Twin 15 hp (11kw)
Amperage: 44A
Voltage: 460V, 3ø, 60 Hz
Power Cord: 50 ft. (15m)
Dust Hose Connection: 6 in. (150mm)
Dimensions: L 77 in. (1950mm) x W 28 in. (720mm) x H 55 in.(1400mm)
Weight: Net 1268 lb. (575kg)

¹Production rates achieved will be affected by variables specific to each job site. These figures are not guarantees of performance. For proper operation, the shot blasting unit must be used in conjunction with an appropriate dust collection device.

Always wear appropriate eye, ear and respiratory protection for the application, as specified by OSHA regulations and your employer. Never operate or maintain equipment before reading and understanding the instructions for operation and maintenance. Obey all safety signs and instructions while operating or maintaining equipment.

Products manufactured and marketed by Blastrac are protected by patents issued or pending in the United States and other countries. Blastrac reserves the right to change the specifications referred to in this literature at any time, without prior notice. Blastrac is a registered trademark owned by Blastrac, NA.

Trust the Original Surface Preparation Experts

BLASTRAC®
800.256.3440 • blastrac.com