

Grinding & Polishing Systems

HEAVY-DUTY, SELF-PROPELLED SCARIFIERS

BMP-335

The Blastrac® BMP-335 scarifiers are heavy-duty machines designed and manufactured for the most demanding of jobs. With variable speed, forward and reverse, these heavy-weight performers can be maneuvered or driven without having the scarifying drum engaged.

An easy-lift system lowers and raises the drum, and fine-height cutting adjustments are stayed in position with controls that are easily accessible to the operator. These units are comfortable to use, easy to move and create minimal vibrations.

Both heavyweight for increased performance, the synchronous-belt driven BMP-335GHY has 2 independent hydraulic brake motors for adjustable feed speed, and the BMP-335EHY features separate, electric independent drive and drum motors. The self-propelled drive system is employed with a unique foot pedestal mechanism.

Both machines can utilize versatile tooling options for job specific applications on surfaces such as concrete, stone, or asphalt. These machines are ideal for removal of hard top layers from soft floors, or for line stripe removal. Either scarifier works virtually dust-free when connected to the BDC-317P or the BDC-3140P dust collector.

Contractors will appreciate the professional quality and durability of the BMP-335EHY and BMP-335GHY surface scarifiers.



Scarifying and milling drum assemblies are shown. These can achieve versatile patterns for texturing or milling with adjustment of the spacers and cutting teeth.

Always wear appropriate eye, ear and respiratory protection for the application, as specified by OSHA regulations and your employer. Never operate or maintain equipment before reading and understanding the instructions for operation and maintenance. Obey all safety signs and instructions while operating or maintaining equipment.

Products manufactured and marketed by Blastrac/Diamatic are protected by patents issued or pending in the United States and other countries. Blastrac/Diamatic reserves the right to change the specifications referred to in this literature at any time, without prior notice. Blastrac and Diamatic are registered trademarks owned by Blastrac, NA.

Blastrac
BMP-335GHY

Blastrac
BMP-335EHY



Totally tungsten milling cutters, or the tungsten-tip steel scarifying cutters add versatility to the BMP-335s.

BMP-335EHY

SPECIFICATIONS:

Cleaning Path: 13.2 in. (335mm)
 Production Capacity: Up to 570 sqft/hr
 Drum Diameter: 8.5 in. (216mm)
 Drum Speed: 1,000 RPM
 Drum Motor: 15 hp
 Drive Motor: 2 hp
 Voltage: 460V, 3 ϕ , 50/60 Hz
 Power Cord: 50 ft.
 Dust Hose Connection: 3 in. (76mm)
 Dimensions: L 59 in. (1498mm) x W 24 in. (609mm) x H 37.5 in. (952mm)
 Weight: 895 lbs (406kg) excluding drum

BMP-335GHY

SPECIFICATIONS:

Cleaning Path: 13.2 in. (335mm)
 Production Capacity: Up to 570 sqft/hr
 Drum Diameter: 8.5 in. (216mm)
 Drum Speed: 1,000 RPM
 Engine: 15 hp Hatz Diesel
 Drum Motor: 15 hp hydraulic
 Drive Motor: 2 hp hydraulic
 Power Cord: n/a
 Dust Hose Connection: 3 in. (76mm)
 Dimensions: L 59 in. (1498mm) x W 24 in. (609mm) x H 37.5 in. (952mm)
 Weight: 895 lbs (406kg) excluding drum

Trust the Original Surface Preparation Experts

BLASTRAC®

800.256.3440 • blastrac.com

1021 06/10 © 2010 Blastrac, NA All rights reserved.