



Shown with an Optional Weight Set

## Stripping, Sanding, Resurfacing & Polishing

The Brute 360 is built for high productivity in the harshest jobs like concrete resurfacing, natural stone polishing, and wood screening and sanding. Designed with the powerful 1.5 HP 180 frame TEFC (Totally Enclosed Fan Cooled) AC motor, fit with 1:11 hardened helical cut gears and an industrial grade steel coupler. This combination of motor and gears weighs 30 pounds more than a standard machine of similar size.

The machine is built with the HAWK 360™ dust pickup system, using a 16 gauge steel, powder-coated brush cover with a 360 degree dust collecting duct and 2" dust exhaust port. All commercial tank vacuums with a 1.5" or 2" hose connect to this port. Remove the heaviest soils by adding the optional 50 lb. weight set with transport lock.

### Power

- 180 frame TEFC dual capacitor AC motor
- 115-230V, 60 Hz power. (50 Hz optional).
- 50 ft., 2-pc. 12-3 SJTOW industrial yellow power cord with twist-lock plug
- Extra heavy duty XHD steel helical-cut 11:1 gears with steel coupler

### Engineered Design

- Proprietary HAWK 360™ brush cover with wrap-around dust guard picks up dusts and debris
- Extra heavy duty steel handle with vacuum hose support
- Heavy duty motor guard protects the motor from impact damage
- Dual steel operating triggers with negative pressure on/off switch
- Thumb-operated safety switch. Comfortable vinyl-dipped foam grips.
- 2" x 6" non-marking load bearing, ball bearing wheels
- Optional (2) 25 lb. removable weight set, with locking pins and transport lock (#A360-17-2 -17"), (#A360-20-2 - 20").

### Safety Features:

- Quiet 66 dB operation. Meets GS42 standard.
- UL/CUL listed



## Specifications

<b>Model</b>	<b>HP1517BRUTE-BDC (Black)</b>	<b>HP1520BRUTE-BDC (Black)</b>
<b>Part #</b>	F38-B (Black)	F41-B (Black)
<b>Model</b>	<b>HP1517BRUTE-CDC (Chrome)</b>	<b>HP1517BRUTE-CDC (Chrome)</b>
<b>Part Number</b>	F38-C (Chrome)	F41-C (Chrome)
<b>Machine Size</b>	17 inch	20 inch
<b>Pad Size</b>	16 inch	19 inch
<b>Pad Speed</b>	165 RPM	165 RPM
<b>Amp Draw</b>	7.9 Amp	8.4 Amp
<b>Machine Wt.</b>	133 lbs.	135 lbs.

## All Sizes

<b>Motor</b>	1.5 HP, 180 frame, TEFC dual capacitor AC motor
<b>Power</b>	115-230V, 60 Hz power (50 Hz optional)
<b>Power Cord</b>	50 ft. 2-piece 12-3 SJTOW yellow industrial power cord w/twist-lock plug
<b>Drive System</b>	Triple-planetary XHD 11:1 helical-cut industrial gears
<b>dB Rating</b>	66 dB - Meets GS42 standard

Subject to Change Without Notice



Handle is 3" Wider than Standard  
The Handle-Mounted Hose Support Carries 1.5" and 2" Vacuum Hoses



Variable Handle Height Adjustment and Transport Lock



The Steel Brush Cover is Built with a 1.5" or 2" Vacuum Port



360° Duct in the Brush Apron Directs Debris to the 2" Vacuum Port