



# H

# A

# W

# K



UL/CUL Approved  
Machine

## Hawk BRUTE Floor Machine with 180-Frame TEFC Motor



(BRUTE)



(TEXHD)



The **Brute** is equipped with a severe duty, planetary triple-idler, all steel helical-cut gear drive, with steel coupler and exclusive 180 frame TEFC motor (Totally Enclosed Motor). TEFC units are ideal for the harshest conditions – dust, moisture, chemicals – and great for sanding or screening, stone care, concrete work, and other applications that require “Brute Force.”

**Note:** These units are NOT equipped with an explosion-proof motor.

### Features

- |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"><li>Twin (dual) capacitor 180 frame TEFC motor (Totally Enclosed Fan-Cooled) motor keeps out dirt, dust, and moisture for longer motor life.</li><li>Virtually indestructible 11:1 gearbox</li><li>Industrial cord with molded plug.</li><li>Low current draw</li><li>UL / CUL - Approved for safe performance</li><li>Thumb operated safety switch</li><li>Negative pressure on/off switch</li><li>Dual steel operating triggers for left or right hand operation</li></ul> | <ul style="list-style-type: none"><li>One-piece chrome, heavy duty steel handle for optimum durability</li><li>Welded frame for rugged, reliable performance</li><li>Non - Marking 5" ball bearing wheels</li><li>Variable position positive lock handle for operator comfort and safety</li><li>Comfort style vinyl handle grips for ease of use</li><li>360 - degree wraparound-and-under snug fit bumper- no tools needed for replacement</li></ul> |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|



# H

## Technical Specifications

Model #	HP1513-180BRUTE	HP1515-180BRUTE	HP1517-180BRUTE	HP1520-180BRUTE
Part #	F0013-180CP	F0006-180CP	F0009-180CP	F0012-180CP
Pad Size	13 inch	15 inch	17 inch	20 inch
Power Source*	115V 60Hz	115V 60Hz	115V 60Hz	115V 60Hz
Motor/HP	180 Frame, 1-1/2 HP TEFC AC Dual Capacitor Motor	180 Frame, 1-1/2 HP TEFC AC Dual Capacitor Motor	180 Frame, 1-1/2 HP TEFC AC Dual Capacitor Motor	180 Frame, 1-1/2 HP TEFC AC Dual Capacitor Motor
Amp Draw	7.2	7.5	7.9	8.4
Gear Box	3-Idler 11:1	3-Idler 11:1	3-Idler 11:1	3-Idler 11:1
Brush RPM	165	165	165	165
Cord**/***	50' 12-3 STJOW	50' 12-3 STJOW	50' 12-3 STJOW	50' 12-3 STJOW
Weight	113 lbs	117 lbs	123 lbs	125 lbs
Shipping Weight	120 lbs	124 lbs	130 lbs	132 lbs

\*230V Available \*\* 75' Cord Available (12-3) \*\*\*100' Cord Available (14-3)

Model #	HP1513-TEXHD	HP1515-TEXHD	HP1517-TEXHD	HP1520-TEXHD
Part #	F0013-180TEXHD	F0006-180TEXHD	F0009-180TEXHD	F0012-180TEXHD
Pad Size	13 inch	15 inch	17 inch	20 inch
Power Source*	115V 60Hz	115V 60Hz	115V 60Hz	115V 60Hz
Motor/HP	180 Frame, 1-1/2 HP TEFC AC Dual Capacitor Painted Motor	180 Frame, 1-1/2 HP TEFC AC Dual Capacitor Painted Motor	180 Frame, 1-1/2 HP TEFC AC Dual Capacitor Painted Motor	180 Frame, 1-1/2 HP TEFC AC Dual Capacitor Painted Motor
Amp Draw	7.2	7.5	7.9	8.4
Gear Box	3-Idler 11:1	3-Idler 11:1	3-Idler 11:1	3-Idler 11:1
Brush RPM	165	165	165	165
Cord**/***	50' 12-3 STJOW	50' 12-3 STJOW	50' 12-3 STJOW	50' 12-3 STJOW
Weight	113 lbs	117 lbs	123 lbs	125 lbs
Shipping Weight	120 lbs	124 lbs	130 lbs	132 lbs

Specifications subject to change without notice.

dB Rating: 66  
Meets GS42  
Requirements

Specifications subject to change without notice.

# K

# W



# H



A0032-1P -- Optional 25#  
Horseshoe Weights (each)  
A0032-3P – Optional 36#  
Horseshoe Weights (each)

A0032-2P  
20# Frame  
Weight



HP0008-3IN-  
BRUTE  
Motor Mounted  
Weight Post Kit



A0028-10P--  
10# Hexigonal weight  
A0028-25P--  
25# Hexigonal weight



**Weighted Diamond  
Pad Driver:**

13"	A0017WTDPD (25#)
15"	N/A
17"	A0010WTDPD (46#)
20"	A0011WTDPD (64#)

**Hawk Scrapers  
(Surface Prep):**

13"	HP0035
15"	N/A
17"	HP0033
20"	HP0034

**Orbitec Diamond  
Driver:**

13"	HP0018
15"	N/A
17"	HP0017
20"	HP0020



**Poly Brush:**

13"	A0020
15"	A0036
17"	A0002
20"	A0003

**Nylon Brush:**

13"	A0016
15"	A0037
17"	A0006
20"	A0007

**Sand Paper Driver:**

13"	N/A
15"	N/A
17"	A0014-HD
20"	A00014-1HD

**Pad Driver:**

13"	A0017
15"	A0034
17"	A0010
20"	A0011

**Pads: ( 5 Per Case)**

Size	Porko	Red	Black
13"	A0025-13P	A0026-13R	A0027-13BK
15"	A0025-15P	A0026-15R	A0027-15BK
17"	A0025-17P	A0026-17R	A0027-17BK
19"	A0025-19P		
20"	A0025-20P	A0026-20R	A0027-20BK



Dust Pickup System For a  
BRUTE Machine

# Hawk Enterprises, Inc.

Elkhart, IN 46514

Distributed By:

Toll Free Phone (888) 289-4295 Local Phone (574) 294-1910  
Toll Free Fax (866) 429-5329 Local Fax (574) 970-0289