

# HiPro 60 H<sub>2</sub>O



## System Made of Aluminum

- Pressure adjustable:** 2.9 - 123 PSI (0.2 - 8 bars)
- Abrasive range:** 30-350 Mesh (2.5 - 0.025 mm)
- Hose length:** 30 ft. (10 m)
- Standard nozzle size:** 0.48-0.5 in. (12 - 15 mm)
- Tank capacity:** 16 gal. / 125 lbs. (60 liter)
- Usage rate:**
- Performance:**
- System height (w/out handle):** 29"
- System width (w/out front legs):** 18" (w/legs 14")
- Packaging (box) dimensions:** 36x30x37"
- Machine net weight (empty tank):** 145 lbs. (65 kg)
- Cleaning surfaces:** steel, aluminum, stainless steel, wood, glass, marble, concrete, masonry, stone, composite materials, etc.

Requires XXX cfm

**IBIX HiPro 60 H<sub>2</sub>O System, including:**  
**0.48-0.5" Nozzle (12-15 mm) Standard**  
**30 ft. hose**  
**Application Gun and Water Nozzle**  
**Filling Funnel w/Sieve**



IBIX HiPro 60 H<sub>2</sub>O  
Nozzle Kit



Water Nozzle



Adjustable Flow



Lance Extension

## AIR CONSUMPTION AT NOZZLE (measured in cubic feet/minute = cfm):

Nozzle	Pressure				
	58 PSI (4 bar)	72.5 PSI (5 bar)	87 PSI (6 bar)	101.5 PSI (7 bar)	116 PSI (8 bar)
Standard 13/32" (10 mm)	139 cfm	153 cfm	167 cfm	183 cfm	195 cfm
<i>Also available for this system:</i>					
Size 9/32" (7 mm)	80 cfm	88 cfm	95 cfm	101 cfm	107 cfm
Size 5/16" (8 mm)	90 cfm	98 cfm	107 cfm	117 cfm	125 cfm
Size 15/32" (12 mm)	200 cfm	220 cfm	240 cfm	264 cfm	280 cfm

**IBIX Compressor Option:**

IBIX VRK520D or equivalent



Informational Chart according to ISO 5167

### Abrasives:

- IBIX STRONG: 30-40 Mesh
- IBIX SPEED BLAST: 60 Mesh
- IBIX MEDIUM: 80 Mesh
- IBIX FINE: 120-150 Mesh
- IBIX EXTRA FINE: 200-350 Mesh
- IBIX CARBON Z5: ~0.212 = ~212 μm
- IBIX CARBON Z6: ~0.106 = ~106 μm

