



This hydraulically driven, forward self-propelled scraper removes the worst of today's soft goods, such as glued-down floors, gummy commercial carpet, VCT, sheet vinyl, rubber tile, linoleum, indoor and outdoor sport surfaces, roofing material, and more. The ergonomic features of this machine reduce operator fatigue while optimizing time and labor savings. The compact design makes it ideal for use in tight spaces.

5280 Specifications

Power Supply	Electric	
Width	17"	43 cm
Height	39"	99 cm
Length	27"	69 cm
Weight	263 lb	119 kg
Removable Weight	37 lb front, 49 lb saddle	16.8 kg front, 22.2 kg saddle
Weight (machine only)	177 lb	80.3 kg
Speed	12-50 ft/min	3.7-15.2 m/min
RPM	1725/1425	
Voltage	115	230
Frequency	60 Hz	50 Hz
HP	1	.746 kW
Amps (full load)	12/6.7	
Noise Emission	77 dB	

Meets the requirements of the Machine Directive 2006/42/EC and EMC Directive 2004/108/EC. It is CE marked.

SAFETY

A. Tie-down/lifting bail

PERFORMANCE

B. Forward self-propelled control

COMFORT

C. Variable speed, 12 to 50 feet per minute

D. Self-contained, limited-maintenance hydraulic fluid

E. Removable 49-pound saddle weight helps increase or decrease down pressure and traction

F. Orbital action rotates the cutting blade to cut through a range of materials over various substrates; extends life cycle of machine while reducing maintenance costs

INCLUDED WITH THE 5280

- Kit 5173 includes:
 - 148 5" x 6" blade
 - 6258-BU 3" x 12" self-scoring blade
 - 6286 3" x 10" heavy-duty blade
 - 7050-200 3" x 6" premium high-tempered blade
 - 7050-202 3" x 10" premium high-tempered blade
 - 5280-137W: 6 mm t-handle wrench
 - Operating and Service Manuals
 - One-year manufacturer's warranty on parts and labor

RECOMMENDED ACCESSORIES

6280-505

- Swivel head rotates to allow continuous contact with the floor

6280-500

- Swivel head allows for continuous contact with the floor and is specifically for razor blades

WALK-BEHIND MACHINE ACCESSORIES



6280-505 SWIVEL HEAD ATTACHMENT

Optional swivel head attachment maintains 100 percent contact between the blade and the surface, maximizing production rates. Rotate the head 180 degrees to self-sharpen the blade during use.

- Holds blades of .062 or .094 thickness
- Works on thin, soft coatings, paint, hard-to-remove gummy or dry adhesives
- Ultimate adhesive removal
- Designed to fit on the **550**, **5280**, and **6280-COM** walk-behind machines

6280-500 SWIVEL HEAD ATTACHMENT FOR RAZOR BLADES

Optional attachment keeps your blade in contact with the surface of the floor.

- Designed to fit on the **550**, **5280**, and **6280-COM** walk-behind machines

6251 LOADING RAMP

- 15" x 6'9"

402311 REPLACEMENT WHEEL PIN

- 5/16 x 2-1/16 replacement wheel pin for the **6280** and **6280HD**

CUTTING HEADS FOR THE 6280HD GLADIATOR

- 7280-6: 6-inch cutting head
- 7280-10: 10-inch cutting head
- 7280-12: 12-inch cutting head
- 7280-14: 14-inch cutting head
- 7280-12RBH: Razor blade head

7280-12RBH

- Razor blade head for **6280HD-COM**



7280-2B ANGLE ATTACHMENT

- 22-degree angle attachment for soft goods removal with the **6280HD**

7280-2C ANGLE ATTACHMENT

- 30-degree angle attachment for hard goods removal with the **6280HD**



402276

- 9 degree angle attachment

7280-4 RETAINER CAP ASSEMBLY

- Replacement assembly for **6280HD** shanks

Blades and Shanks

The industry's largest selection of scraper blades, including our patented line, is always in stock and available. Our patented carbide blades are engineered for the toughest ceramic and hardwood removal applications and are gaged at a specific Rockwell hardness for maximum efficiency and longevity.



ELECTRIC POWER



BATTERY POWER



PROPANE