



5625 Specifications

Power Supply	Propane	
Width*	26"	66 cm
Height	51"	129.5 cm
Length*	58"	147 cm
Weight**	1,822 lb	826.4 kg
Removable Weight	370 lb front, 75 lb rear	167.8 kg front, 34 kg rear
Weight (machine only)	1,377 lb	624.6 kg
Speed	up to 200 ft/min	up to 61 m/min
HP	25	18.6 kW

5625DL Specifications

Power Supply	Propane	
Width*	26"	66 cm
Height	52.25"	133 cm
Length*	63"	160 cm
Weight**	1,822 lb	826.4 kg
Removable Weight	370 lb front, 75 lb rear	167.8 kg front, 34 kg rear
Weight (machine only)	1,377 lb	624.6 kg
Speed	up to 200 ft/min	up to 61 m/min
HP	25	18.6 kW

*Measurements are without tooling attached.

**Weight may vary depending on fill level and size of propane tank on machine.

The 5625 is available with or without the Dual Lift. The Dual Lift feature adds operator controls for adjusting blade pitch and angle while remaining seated.

SAFETY

- A.** Automatic kill switch is triggered when the operator seat is vacant
- B.** Liquid-cooled Kawasaki engine is re-engineered with National's exclusive catalytic design for the industry's lowest emissions
- C.** Front debris deflector protects machine from loose material

COMFORT

- D.** Ergonomic design includes movable foot pegs, taller handles, and an adjustable seat and armrests that allow for optimal operator comfort and the best possible line of sight
- E.** Hinged hood system for easy-access maintenance

PERFORMANCE

- F.** Precise hydraulic steering for maneuvering in tight spaces, zero turn radius, and continuous torque for higher removal rates and greater productivity
- G.** Quick-change swivel head blade holder
- H.** Optional dual-lift, hydraulic slide plate adjusts blade pitch and angle for continuous contact with the floor
- I.** Larger/deepened forklift pockets
- J.** Nonmarking tires
- K.** Compact design fits through standard door frames and elevator doors
- L.** Improved exhaust system meets federal OSHA regulations
- M.** Front caster wheels allow increased maneuverability in tight spaces
- N.** 12-volt LED light for increased visibility on the jobsite

INCLUDED WITH THE 5625

- 5110-100: Transport Wheels
- 402929: 3/4 x 1-1/8 Wrench
- Operating and Service Manuals
- Kit 5175 includes:

- 6277-BU: 45 degree, 3" x 12" self-scoring, bevel up
- 6284: 3" x 12" heavy-duty blade

- 6285: 3" x 6" heavy-duty blade
- 6286: 3" x 12" heavy-duty blade
- 7050-12: 12" cutting head
- 7050-6: 6" cutting head
- 7079-2: 2" x 6" angle shank w/carbide tip
- 74854: Weight, 37 pounds (10) (front)
- 5110-404: Weight, 75 pounds (1) (rear)

- 7050-P: Propane tanks (2)
- 75007: CO detector (2)
- 75008: Clip (2)
- 5700-88: Hour meter
- 75005: Fire extinguisher
- One-year manufacturer's warranty on parts and labor

RIDE-ON MACHINE ACCESSORIES

SWIVEL CUTTING HEAD ASSEMBLIES

Tough swivel heads rotate to ensure continuous blade contact with the floor. Flip it over to use the second sharp edge without having to remove it from the machine. Available in a full range of sizes, to fit any job.

Fits the following products: **4230, 5110, 5200QL, 5625, 5000, 5700®, 2900, 7700, and 8000**

- 7050-8RBH: 8-inch razor blade head
- 7050-12RBH: 12-inch razor blade head
- 7050-14RBH: 14-inch razor blade head
- 7050-6: 6-inch cutting head
- 7050-8: 8-inch cutting head
- 7050-10: 10-inch cutting head
- 7050-12: 12-inch cutting head
- 7050-14: 14-inch cutting head
- 7050-27: 27-inch cutting head
- 402239: 3/8 x 1-1/2 replacement retaining pin secures cutting head assemblies
- 73422: Cutting Head Bolt

403228 HYDRAULIC SLIDE PLATE

Adjust the height of the slide plate using the hydraulic hand control for precise angling. Comes standard on **7700** and **8000** ride-on scrapers.

- No lifting, dismantling, or manual labor required to adjust plate height
- Adds 200 pounds of weight to the front of the machine, where it is most effective
- Available as an option on new ride-on machines or as a kit for existing ride-on machines

7050-15 CUTTING HEAD EXTENSION

- Reaches under tight areas
- 17-inch length
- Cutting head sold separately

7074 TILE BOX

- For fast cleanup, debris collection, and removal, this box is made of high-abrasion alloy for long-lasting durability
- For use with 7050-27
- Size: 5 inches deep, 27 inches wide, 6 inches tall
- Cutting head sold separately

5110-100 TRANSPORT WHEELS

Quick and easy to attach, this assembly creates stability and safe transportation over any surface. Fits all National-brand ride-on machines.

70639 WHEEL COVERS

- Protective cover slips easily on and off wheels
- Sold individually
- Fits all National-brand ride-on machines

5700-88 HOUR METER

- Monitors the hours of usage
- Fits all National-brand ride-on machines

400321 ARMREST

Fits all current National-brand ride-on machines

75007 LAPEL CARBON MONOXIDE MONITOR

Ships with the **5625** and **8000** machines. For jobsites where carbon monoxide could be present, this badge can detect as little as 100 ppm carbon monoxide gas at approximate relative humidity range of 33 to 50 percent. If the humidity is very high, it can detect concentrations as low as 20 ppm. The presence of CO changes the sensor from red to gray/black as the concentration levels increase. Once the detector is exposed to fresh air, it will return back to red. Once opened, the badge lasts approximately 90 days. Adhesion strip on the back, or optional lapel clip mounts almost anywhere.

75008 LAPEL CARBON MONOXIDE CLIP

5204 BATTERY POWER PACK

Designed for high vibration and shock load, this battery pack makes the **5200QL** a true "cordless" machine.

The removable batteries can be changed so there is no need for downtime while recharging.

- Unique design eliminates acid spilling
- Designed for high vibration
- Can be charged from 115 volt

This battery pack runs to a deeper discharge than typical 75-amp hour battery packs and has the ability to take a rapid charge without affecting the cycle life.

BATTERY CHARGER

Exclusively designed to work with the **5200QL**. This high-performance battery charger is for use in demanding applications where optimal performance and service life are critical. It provides a complete charge in a short amount of time and works specifically with the 5204 power pack. Its 48-volt charger runs on 115-volt power.

- 5212: 48 V, 60 Hz, 115 V
- 5212-W: 48 V, 50-60 Hz, 230 V
- 404062: 48 V, 50 to 60 Hz, 100 V (for Japan Only)

WOOD-SCORING SCARIFIER DRUM

This wood scoring drum attaches to National's **Spartan 220** scarifier. It is an 8" drum, with three or five scoring blades. Using this on your scarifier eliminates the need to get down on your hands and knees to use a circular saw to score the wood.

- 402192: Drum with Three Blades
- 402191: Drum with Five Blades

73507-1

- 7-foot, 12-gauge extension cord for charging



ELECTRIC POWER



BATTERY POWER



PROPANE